



SonicWall to WatchGuard Conversion Chart

| If people ask for | Offer them a | User Counts | Throughput | | | | | VPN Licenses Concurrent Licensing | | Physical Characteristics | | | | |
|---------------------|----------------------|-------------|------------|---------------------|--------------------------|---------------------------------|----------|--------------------------------------|------------------------------------|--------------------------|----------------------|--------------------|-------------|-------------|
| | | | Sonicwall | WatchGuard Firewall | Recommended not licensed | Firewall <i>No filtering</i> | AV | IPS | UTM <i>All Services Enabled</i> | VPN | Site to Site Tunnels | Mobile SSL / IPsec | 1 Gig Ports | Fiber Ports |
| TZ 50H0 | Firebox T15 | 5 | 400 Mbps | 120 Mbps | 160 Mbps | 90 Mbps | 150 Mbps | 5 | 5 | 3 | 0 | Tabletop | No | 0 |
| TZ 300/400 | Firebox T35 | 20 | 940 Mbps | 325 Mbps | 573 Mbps | 278 Mbps | 560 Mbps | 25 | 25 | 5 (1 PoE) | 0 | Tabletop | No | 0 |
| TZ 500 | Firebox T55 | 35 | 1 Gbps | 636 Mbps | 636 Mbps | 523 Mbps | 360 Mbps | 40 | 50 | 5 (1 PoE) | 0 | Tabletop | No | 0 |
| TZ 600 | Firebox T70 | 60 | 4 Gbps | 1.2 Gbps | 1.5 Gbps | 1.1 Gbps | 740 Mbps | 50 | 60 | 8 | 0 | Tabletop | No | 0 |
| NSA 2600 | Firebox M200 | 60 | 3.2 Gbps | 620 Mbps | 1.4 Gbps | 515 Mbps | 1.2 Gbps | 50 | 75 | 8 | 0 | 1U Rack | No | 0 |
| NSA 3600 | Firebox M370 | 150 | 8.0 Gbps | 3.0 Gbps | 4.8 Gbps | 2.6 Gbps | 4.6 Gbps | 100 | 100 | 8 | 0 | 1U Rack | No | 0 |
| NSA 4600 | Firebox M470 | 350 | 19.6 Gbps | 3.5 Gbps | 5.7 Gbps | 3.1 Gbps | 5.2 Gbps | 250 | 200 | 8 | Optional | 1U Rack | No | 1 |
| NSA 5600 | Firebox M440 | 450 | 6.7 Gbps | 2.2 Gbps | 2.2 Gbps | 1.6 Gbps | 3.2 Gbps | 300 | 300 | 25 | 2x10g SFP+ | 1U Rack | Optional | 0 |
| | Firebox M570 | 500 | 26.6 Gbps | 5.4 Gbps | 8.0 Gbps | 4.4 Gbps | 5.8 Gbps | 500 | 500 | 8 | Optional | 1U Rack | No | 1 |
| | Firebox M670 | 750 | 34 Gbps | 6.2 Gbps | 10.4 Gbps | 5.4 Gbps | 7.6 Gbps | 750 | 750 | 8 | Optional | 1U Rack | No | 1 |
| NSA 6600 | Firebox M4600 | 1500 | 40 Gbps | 9 Gbps | 13 Gbps | 8 Gbps | 10 Gbps | 5000 | 10,000 | 8 | Optional 4x10G | 1U Rack | Yes | 2 |
| SM 9200-9800 | Firebox M5600 | 7500 | 60 Gbps | 12 Gbps | 18 Gbps | 11 Gbps | 10 Gbps | Unrestricted | Unrestricted | 8x1G + 4x10G | Optional 4x10G | 1U Rack | Yes | 2 |

Firebox M470, 570 and 670 ship with one empty bay that can accommodate one of the following: 4 x 10 Gb fiber, 8 x 1 Gb fiber, or 8 x 1 Gb copper

Firebox M4600 and M5600 throughput rates are determined using base configuration + 4 x 10 Gb ports. Two empty bays can accommodate any combination of the following: 4 x 10 Gb fiber, 8 x 1 Gb fiber, 2 x 40 Gb fiber, 8 x 1 Gb copper.

Note: Recommended user count refers to number of connected devices behind firewall in office or organization. Max number of users on firewall at any one time is expected to be roughly half this amount. Throughput is measured using 1518 byte packets through multiple port pairs. Actual network performance may vary depending on environment.